

Модуль Cisco C6800-8P40G

C6800-8P40G



Описание

8-портовый модуль 40GE QSFP+ для шасси коммутатора Cisco Catalyst C6807-XL.

Основные особенности:

- 8 портов 40GE QSFP+
- Переопределение: 8 портов 2:1
- Память по умолчанию 2GB (максимум)
- Поставляется с модулем DFC4
- Таблица MAC адресов 128K
- Поддержка Jumbo Frame 9216 байт

Общие

| | |
|---|--|
| Тип устройства | Карты расширения |
| Линейка Cisco | Catalyst 6800 |
| Совместимая платформа | Шасси C6807-XL |
| Поддерживаемый тип интерфейсов модульного коммутатора | Интерфейсы 40Gbase-X QSFP+ |
| Совместимость с управляющими модулями | C6800-SUP6T VS-S2T-10G VS-S2T-10G-XL |

Доп. описание

| Non-XL | XL |
|---|--|
| 256K IPV4 and MPLS forwarding entries, 128K IPV6 entries 64K IPV4/IPV6 Multicast routes 64K ACL entries (shared between QoS and security) 1M NetFlow entries (with 2 forwarding engines) | 1M IPV4 and MPLS forwarding entries, 512K IPV6 entries 64K IPV4/IPV6 Multicast routes 256K ACL entries (shared between QoS and security) 2M NetFlow entries (with 2 forwarding engines) |



nag
Следуй за экспертом

ООО «НАГ»
+7 (343) 379-98-38
sales@nag.ru