



ООО «НАГ»
+7 (343) 379-98-38
sales@nag.ru

Коммутатор Cisco Nexus N9K-C92304QC

N9K-C92304QC



Описание

В комплект входит:

- Блок питания AC Port Side Intake (NXA-PAC-650W-PI) или Port Side Exhaust (NXA-PAC-650W-PE) - 2 шт.
- Блок вентиляторов Port Side Intake (N9K-C9300-FAN3) или Port Side Exhaust (N9K-C9300-FAN3-B) - 2 шт.

Модель блоков питания и вентиляторов уточняйте у менеджера.

Крепления в стойку и дополнительные лицензии в комплект не входят!

Обзор продукта

Платформа Cisco Nexus 9200 серии состоит из ведущих в отрасли коммутаторов центров обработки данных с фиксированной конфигурацией, line-rate 2 и 3 уровня, и функционалом который поддерживает корпоративные и коммерческие приложения, поставщиков услуг хостинга и облачные вычисления. Эти коммутаторы поддерживают широкий диапазон скоростей портов с гибкими комбинациями подключения 1/10/25/40/50/100-Гбит/с в компактных форм-факторах.

Основные особенности Cisco Nexus N9K-C92304QC:

- 4 ядерный CPU Intel®
- Память DRAM 16 GB
- SSD drive 64 GB
- 56 портов 40 Гбит/с QSFP+, 8 портов 100 Гбит/с до 16 портов могут работать в режиме 4 x 10 Гбит/с с использованием breakout кабеля (до 64 портов 10 Гбит/с)
- Пропускная способность 6.1 Тбит/с
- Скорость пересылки пакетов более 4.8 миллиардов пакетов в секунду (bps)
- Буфер 30 МБ
- Wire-rate уровня 2 и 3
- 2 блока питания (AC или DC), 2 блока вентиляторов
- Прямое (Port-side exhaust) и обратное (Port-side intake) охлаждение

Общие

Размещение

Монтируемые в стойку

Тип коммутатора

Тип коммутатора

Управляемый L3

Линейка Cisco

Nexus 9000

Интерфейсы

Тип основных портов

40GigabitEthernet QSFP+

Интерфейсы 40GBase-X

56

Интерфейсы 100GBase-X

8

Консольный порт

RJ45

Количество основных портов

56

Тип Uplink портов

100GigabitEthernet QSFP28

Питание

Напряжение питания

220V AC

Допустимое напряжение питания

100-240V AC

L2 функционал

Количество VLAN

3967

Размер таблицы MAC адресов

92000

Количество правил ACL

4000

Агрегирование портов

LACP

Доп. описание

Дополнительные лицензии и функционал (заказываются отдельно, уточняйте у менеджера)

Feature License	Product ID	Feature Name
Enterprise Services Package LAN_ENTERPRISE_SERVICES_PKG	N95-LAN1K9 (for Cisco Nexus 9500 Series switches) N93-1G-LAN1K9 (for the Cisco Nexus N9K-C9348GC-FXP switch) N93-LAN1K9 (for Cisco Nexus 9200, 9300, 9300-EX, and 9300-FX/FX2 Series switches, except the Cisco Nexus N9K-C9348GC-FXP switch) N93-LAN1K9-XF2 (for the Cisco Nexus 9364C	Open Shortest Path First (OSPF) Protocol Border Gateway Protocol (BGP) Intermediate System-to-Intermediate System (IS-IS) Protocol (Layer 3 only) Protocol Independent Multicast (PIM), which includes sparse mode, bidirectional mode, and Source Specific Multicast (SSM) mode Multicast Source Discovery Protocol (MSDP) Policy-Based Routing Generic Routing Encapsulation (GRE) Tunnels Enhanced Interior Gateway Routing Protocol (EIGRP) VRF route leaking VXLAN BGP EVPN Non-blocking multicast (NBM) - for the IP fabric for media solution.



	and 9300-GX switches)	Note The IP fabric for media solution also requires the N93-LAN1K9 or N95-LAN1K9 license for multicast.
VPN Fabric License	N95-FAB1K9 N93-FAB1K9	InterAS option B Layer 3 EVPN over segment routing MPLS MPLS Layer 3 VPN Pervasive Load Balancing (PLB) Tenant Routed Multicast VXLAN EVPN Multi-Site Enhanced PBR (EPBR)
Network Services Package NETWORK_SERVICES_PKG	N95-SERVICES1K9 N93-SERVICES1K9	iCAM Intelligent Traffic Director (ITD) Non-blocking multicast (NBM) - for the IP fabric for media solution. Note The IP fabric for media solution also requires the N93-LAN1K9 or N95-LAN1K9 license for multicast. Smart channel Note Beginning with Cisco Nexus NX-OS 9.3(5), Catena is no longer available. However, Catena is available with the Essentials license package of earlier releases.
FCoE NPV Package FCOE_NPV_PKG	N93-16Y-SSK9 (up to 16 ports) N93-48Y-SSK9 (all 48 ports)	SAN switching, FC NPV, or FCoE NPV Note SAN switching, FC NPV, and FCoE NPV require both the FC_PORT_ACTIVATION_PKG and SAN_ENTERPRISE_PKG licenses. For more information, see the Cisco Nexus 9000 Series NX-OS SAN Switching Configuration Guide and the Cisco Nexus 9000 Series NX-OS FC-NPV and FCoE-NPV Configuration Guide.