



ООО «НАГ»  
**+7 (343) 379-98-38**  
sales@nag.ru



## Модуль Cisco SM-SRE-910-K9

SM-SRE-910-K9

### Описание

- Комплект поставляется со штатными средствами удаленного управления Cisco (без установленных приложений)
- DRAM 1x4Gb, HDD 2x500Gb входят в комплект

[Описание на сайте производителя](#)

Производитель:  
[Cisco](#)

| Product part number                 | SM-SRE-710-K9                         | SM-SRE-910-K9                              |
|-------------------------------------|---------------------------------------|--------------------------------------------|
| Form factor                         | SM                                    | SM                                         |
| CPU                                 | Intel Core2 Solo, 1.86 GHz            | Intel Core2 Duo, 1.86 GHz                  |
| DRAM                                | 4 GB                                  | 4 GB (default) or 8 GB                     |
| Compact Flash memory                | 2-GB internal USB flash-memory module | 2-GB internal USB flash-memory module      |
| Hard disk                           | One 500-GB SATA 7200 rpm              | Two 500-GB SATA<br>(1 TB in non-RAID mode) |
| Hot-swappable hard disk drive (HDD) | None                                  | Yes                                        |



ООО «НАГ»  
**+7 (343) 379-98-38**  
sales@nag.ru

|                                                   |                                                                                  |                                                                                  |
|---------------------------------------------------|----------------------------------------------------------------------------------|----------------------------------------------------------------------------------|
| RAID support                                      | None                                                                             | RAID 0 or 1 (application dependant)                                              |
| Internal network interfaces                       | Gigabit Ethernet connectivity to router backplane                                | Gigabit Ethernet connectivity to router backplane                                |
| External network interfaces                       | One USB connector                                                                | One USB connector                                                                |
|                                                   | One RJ-45 Gigabit Ethernet connector                                             | One RJ-45 Gigabit Ethernet connector                                             |
| Router platforms                                  | Cisco 2911, 2921, 2951, 3925, 3925E, 3945, and 3945E Integrated Services Routers | Cisco 2911, 2921, 2951, 3925, 3925E, 3945, and 3945E Integrated Services Routers |
| Cisco IOS Software (on router)                    | Release 15.1(4)M                                                                 | Release 15.1(4)M                                                                 |
| Embedded hardware-based cryptography acceleration | No                                                                               | Yes                                                                              |
| Power consumption (maximum)                       | 35W                                                                              | 50W                                                                              |
| Dimensions (H x W x D)                            | 1.58 x 7.44 x 7.5 in.                                                            | 1.58 x 7.44 x 7.5 in.                                                            |
|                                                   | (4 x 18.9 x 19.1 cm)                                                             | (4 x 18.9 x 19.1 cm)                                                             |
| Shipping dimensions (H x W x D with packaging)    | 9.5 x 7.5 x 2.5 in.                                                              | 9.5 x 7.5 x 2.5 in.                                                              |
|                                                   | (24.1 x 19.1 x 6.4 cm)                                                           | (24.1 x 19.1 x 6.4 cm)                                                           |
| Maximum weight                                    | 2.5 lb (1.1 kg)                                                                  | 2.5 lb (1.1 kg)                                                                  |
| Operating temperature                             | 32 to 104°F (0 to 40°C) normal                                                   | 32 to 104°F (0 to 40°C) normal                                                   |
|                                                   | 23 to 131°F (-5 to +55°C) short term                                             | 23 to 131°F (-5 to +55°C) short term                                             |
| Humidity                                          | 10 to 85% operating                                                              | 10 to 85% operating                                                              |
| Temperature                                       | -4 to 149°F (-20 to +65°C)                                                       | -4 to 149°F (-20 to +65°C)                                                       |
| Relative humidity                                 | 5 to 95%                                                                         | 5 to 95%                                                                         |

## Общие

Тип устройства

Поддерживаемый тип интерфейсов маршрутизатора

Линейка Cisco

Карты расширения

Интерфейсы 10/100/1000Base-T

Модули SM, NM, NIM, EM, EVM